



Europe / Middle East / Africa

FUJIFILM Optical Devices Europe GmbH
Fujistr. 1, 47533 Kleve, Germany
TEL: +49 (0)2821 / 7115-400 FAX: +49 (0)2821 / 7115-200
<http://www.fujifilm.eu/fujinon>
E-mail: cctv_eu@fujifilm.com

FUJIFILM Middle East

Downtown Jebel Ali
Dubai, UAE
TEL: +971-52-1056367
<http://www.fujifilm-me.com/en/products/optical-devices>

Japan / North East Asia

FUJIFILM Corporation
Optical Device & Electronic Imaging Products Div.
1-324 Uetake, Kita-ku, Saitama City Saitama, 331-9624, Japan
TEL: +81-48-668-2152 FAX: +81-48-667-7924
<https://www.fujifilm.com/jp/ja/>

Oceania

FUJIFILM AUSTRALIA PTY LTD
54 Waterloo Road, Macquarie Park, N.S.W. 2113, Australia
TEL: +61-2-9466-2600 FAX: +61-2-9466-2621
<http://www.fujifilm.com.au/>

North & Latin America

FUJIFILM North America Corporation
Optical Devices Division
10 High Point Drive, Wayne, NJ 07470
TEL: +1-973-633-5600 FAX: +1-973-633-5216
<http://www.fujifilmusa.com>

Hong Kong / Taiwan

FUJIFILM Hong Kong Limited
Optical Device Division
Unit 1908-1911, 19/F., CDW Building,
388 Castle Peak Road, Tsuen Wan, N.T., Hong Kong
TEL: +852-2376-0998 FAX: +852-2724-1118

Southeast Asia & West Asia

FUJIFILM ASIA PACIFIC PTE LTD.
10 New Industrial Road, Fujifilm Building, Singapore 536201
TEL: +65-6383-9933 FAX: +65-6383-5666
<http://www.fujifilm.com.sg/>

Authorized Fujifilm Service Agent.

Due to a continuous process of product improvement, design and specifications are subject to change without notice.
All photos, illustrations, drawings and other images in this brochure are intended for illustrative purpose only.



Be certain to read the instructions for use before using any equipment.


FFBX2021.02-K



FUJINON
Machine Vision Lenses



Product Line-up



Contents

	PAGE
■ CF-ZA-1S series 23MP, 1.1"	04
■ HF-12M series 12MP, 2/3"	06
■ HF-XA-5M series 5MP, 2/3"	07
■ HF-HA-1S series 1.5MP, 1/2"-2/3"	08
■ HF-SA series 5MP, 2/3"	10
■ CF-HA series 1.5MP, 1"	11
■ TF series 3CCD, 1/3"	12
■ FE185 series Fisheye lens	13
■ Shooting Range Chart	14

Please refer to the details on page 3 and 4.



4D High Resolution(P3)



Anti-Shock and Vibration(P3)



High Relative Illumination(P4)


Technologies supporting FUJINON lenses




4D High Resolution performance

- The "4D High Resolution" is the FUJINON lenses' unique performance. It maintains a high level of consistent image sharpness at the center as well as around the edges while mitigating resolution degradation that typically occurs when changing a working distance or aperture value. This enables the stable delivery of high-resolution images under a wide variety of installation and shooting conditions.

General machine vision lenses




4D High Resolution lenses



Anti Shock & Vibration

Anti-Shock : suppresses the optical axis shifts to less than 10µm.

- In the case of ordinary machine vision lenses, the optical axis shifts occur when the lens elements move from their initial position due to shocks. This affects the precise measurement performance of the lens. FUJINON's original^{*1} Anti-Shock design suppresses the optical axis shifts to less than 10µm even when given shocks up to 10G^{*2}.



Axis shift when given repeated shocks

Anti-Vibration : maintains high resolution

- The ordinary machine vision lenses have problems of toughness under working environments with vibration. FUJINON Anti-Vibration lenses have passed severe vibration tests conforming to IEC60068-2-6 and maintain superb resolution.



^{*1}: Patent applied for
^{*2}: Maximum impact tolerance varies by model

Thorough quality control on individual units

- Individual lens units are tested for their optical performance at the factory. Serial No information on the lens is an evidence of the complete quality management. (CF-ZA-1S series, HF-12M series and HF-XA-5M series)




CF-ZA-1S series, 1.1"-4/3"^{*1}, 2.5μm, 23MP



High Relative Illumination


- The advancement of image sensors for Machine Vision tends to larger sensors and smaller pixels. These sensors require a strong light transmission and a small Chief Ray Angle (CRA) so that the sufficient light reaches vertically on the photodiodes of each pixel. CF-ZA-1S series adopts rear lens groups with a large diameter enabled by FUJINON's high-precision assembly technology and achieves a CRA below 5°. This guarantees a high relative illumination across the entire image without vignetting.

- This series eliminates the need for luminance correction with image processing that just amplifies the noise.



Lens with large CRA

Peripheral light ratio: 30%




CF-ZA-1S Series

Peripheral light ratio: 80%

4D High Resolution performance

- Thanks to the 4D High Resolution Design, the resolving power remains consistently high from the center of the image to the edges, even at changing working distances or aperture settings.
- The CF-ZA-1S series draws out the full capability of cameras equipped with a 1.1" sensor with 3.45 μm pixel pitch (equivalent to 12 MP) across the entire frame. These lenses are the perfect choice especially for IMX253 (1.1" type sensor) and IMX225 (1" type sensor).
- The series supports next generation sensors with 1.1" optical format and 2.5μm pixel pitch (equivalent to 23 MP).

"4D High Resolution" lenses General machine vision camera




Compact size of only 39mm outer diameter

- Despite the support of sensors with large 1.1" format, all models of the CF-ZA-1S series offer a uniform diameter of only 39mm and are therefore no larger than standard machine vision cameras. Only the 8mm focal length CF8ZA-1S is slightly larger with a diameter of 54mm in the front lens.




- Thanks to the 3 holes on the lens barrel for fixing iris and focus positions, the most suitable hole can be selected for each application.
- By adopting an internal mechanical focus, the overall length of lens will not change when focused.
- The introduction of a focusing indicator at the working distance of 50cm enables efficient detection of cameras' flange back deviation.




	Anti Shock & Vibration					
CF8ZA-1S	CF12ZA-1S	CF16ZA-1S	CF25ZA-1S	CF35ZA-1S	CF50ZA-1S	
Focal length [mm]	8	12	16	25	35	50
Iris range [F. no]	F1.8-F16	F1.8-F16	F1.8-F16	F1.8-F16	F1.8-F16	F2.4-F16
Angle of view	85.7°x67.5°	62.5°x47.8°	47.3°x36.1°	32.9°x24.8°	23.0°x17.3°	16.6°x12.5°
Working Distance*1 [mm]	∞-100	∞-100	∞-100	∞-100	∞-200	∞-200
Operation of focus	Manual	Manual	Manual	Manual	Manual	Manual
Operation of iris	Manual	Manual	Manual	Manual	Manual	Manual
Filter thread [mm]	M52x0.75	M37.5x0.5	M37.5x0.5	M37.5x0.5	M37.5x0.5	M37.5x0.5
Mount	C-mount	C-mount	C-mount	C-mount	C-mount	C-mount
Weight (approx.) [g]	180	180	180	170	165	155
Sensor size (std.)*2	1.1"(2.5μm)	1.1"(2.5μm)	1.1"(2.5μm)	1.1"(2.5μm)	1.1"(2.5μm)	1.1"(2.5μm)
Sensor size (max.)*3	1.2"(2.74μm)	1.2"(2.74μm)	1.2"(2.74μm)	4/3"(3.45μm)	4/3"(3.45μm)	4/3"(3.45μm)
CRA (Chief Ray Angle)	4.5	4.5	4.9	2.7	4.5	4.8
TV distortion [%]	-4.81	-2.82	-0.80	-0.83	-0.32	-0.17
Dimension [mm]	Ø54x67	Ø39x67.6	Ø39x67.6	Ø39x67.3	Ø39x67.3	Ø39x68


CF8ZA-1S




CF12ZA-1S




CF16ZA-1S




CF25ZA-1S



CF35ZA-1S



CF50ZA-1S



HF-12M series, 2/3"-1"*, 2.1μm, 12MP

Maximum sensor size: 8mm/12mm=2/3", 16mm/25mm=1/1.2", 35mm=1"



- Low distortion
- Compact design



	Anti Shock & Vibration				
Focal length [mm]	8	12	16	25	35
Iris range [F. no]	F1.8-F22	F1.8-F22	F1.8-F22	F1.8-F22	F2.0-F22
Angle of view : 2/3"	56.9°x43.9°	39.3°x30.0°	30.8°x23.3°	20.0°x15.1°	14.7°x11.0°
Working Distance*1 [mm]	∞-100	∞-100	∞-100	∞-100	∞-200
Operation of focus	Manual	Manual	Manual	Manual	Manual
Operation of iris	Manual	Manual	Manual	Manual	Manual
Filter thread [mm]	M30.5x0.5	M30.5x0.5	M30.5x0.5	M30.5x0.5	M30.5x0.5
Mount	C-mount	C-mount	C-mount	C-mount	C-mount
Weight (approx.) [g]	95	85	90	85	85
Sensor size (std.)*2	2/3"(2.1μm)	2/3"(2.1μm)	2/3"(2.1μm)	2/3"(2.1μm)	2/3"(2.1μm)
Sensor size (max.)*3	2/3"(2.1μm)	1/1.2"(4.5μm)	1/1.2"(4.5μm)	1/1.2"(4.5μm)	1"(4.5μm)
TV distortion [%]	-1.03	0.18	-0.03	0.02	0.01
Dimension [mm]	ø33x48.5	ø33x52.5	ø33x52.5	ø33x53.1	ø33x53.1

HF-XA-5M series, 2/3"-1.1"*, 3.45μm, 5MP

Maximum sensor size: 6mm/8mm=2/3", 12mm/16mm/25mm/35mm=1/1.2", 50mm=1.1"




- Compact design




	Anti Shock & Vibration	HF6XA-5M	HF8XA-5M	HF12XA-5M	HF16XA-5M	HF25XA-5M	HF35XA-5M	HF50XA-5M	Anti Shock & Vibration
Focal length [mm]	6	8	12	16	25	35	50		
Iris range [F. no]	F1.9-F16	F1.6-F16	F1.6-F16	F1.6-F16	F1.6-F16	F1.9-F16	F2.4-F16		
Angle of view : 2/3"	74.7°x58.1°	58.4°x44.6°	40.1°x30.3°	31.4°x23.7°	20.0°x15.0°	14.2°x10.7°	10.4°x7.8°		
Working Distance*1 [mm]	∞-100	∞-100	∞-100	∞-100	∞-100	∞-200	∞-200		
Operation of focus	Manual	Manual	Manual	Manual	Manual	Manual	Manual		
Operation of iris	Manual	Manual	Manual	Manual	Manual	Manual	Manual		
Filter thread [mm]	M37.5x0.5	M25.5x0.5	M25.5x0.5	M25.5x0.5	M25.5x0.5	M25.5x0.5	M30.5x0.5		
Mount	C-mount	C-mount	C-mount	C-mount	C-mount	C-mount	C-mount		
Weight (approx.) [g]	100	79	79	71	72	60	95		
Sensor size (std.)*2	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)		
Sensor size (max.)*3	2/3"(3.45μm)	2/3"(3.45μm)	1/1.2"(4.5μm)	1/1.2"(4.5μm)	1/1.2"(4.5μm)	1/1.2"(4.5μm)	1.1"(4.5μm)		
TV distortion [%]	-2.88	-1.99	-1.26	-0.60	-0.07	0.10	0.01		
Dimension [mm]	ø39x51	ø29.5x51.5	ø29.5x51.5	ø29.5x46	ø29.5x46.5	ø29.5x41.5	ø33x66.5		


HF818-12M




HF1218-12M




HF1618-12M




HF2518-12M




HF3520-12M




HF6XA-5M




HF8XA-5M




HF12XA-5M




HF16XA-5M




HF25XA-5M



HF35XA-5M



HF50XA-5M



*1 From front of lens barrel. *2 Sensor size(std.): Ideal size to maximize the target resolution.

*3 Sensor size(max.): Adaptable sensor size varies depending on the model. Please check the amount of light and resolution on the edges pertaining to your particular application.

*1 From front of lens barrel. *2 Sensor size(std.): Ideal size to maximize the target resolution.

*3 Sensor size(max.): Adaptable sensor size varies depending on the model. Please check the amount of light and resolution on the edges pertaining to your particular application.

HF-HA-1S series, 1/2"-2/3", 6.2μm, 1.5MP

**Anti
Shock &
Vibration**

- Wide range of focal lengths with 8 models
- Compact design with an external diameter of 29.5mm*
- Large maximum aperture
- Short Minimum Object Distance


* HF75HA-1S has a diameter of 31.5mm




Anti Shock & Vibration	Anti Shock & Vibration	Anti Shock & Vibration	Anti Shock & Vibration
DF6HA-1S	HF9HA-1S	HF12.5HA-1S	HF16HA-1S
Focal length [mm]	6	9	12.5
Iris range [F. no]	F1.2-F16	F1.4-F16	F1.4-F16
Angle of view	57.3°×43.8°(1/2")	53.3°×40.5°(2/3")	39.2°×29.4°(2/3")
Working Distance*1 [mm]	∞-10	∞-40	∞-20
Operation of focus	Manual	Manual	Manual
Operation of iris	Manual	Manual	Manual
Filter thread [mm]	M27×0.5	M27×0.5	M25.5×0.5
Mount	C-mount	C-mount	C-mount
Weight (approx.) [g]	50	50	40
Sensor size (std.)*2	1/2"(4.5μm)	2/3"(6.2μm)	2/3"(6.2μm)
Sensor size (max.)*3	1/2"(4.5μm)	2/3"(6.2μm)	2/3"(6.2μm)
TV distortion [%]	-1.84	-2.00	-1.95
Dimension [mm]	ø29.5×36.7	ø29.5×35	ø29.5×29.5

Anti Shock & Vibration	Anti Shock & Vibration	Anti Shock & Vibration	Anti Shock & Vibration
HF25HA-1S	HF35HA-1S	HF50HA-1S	HF75HA-1S
Focal length [mm]	25	35	50
Iris range [F. no]	F1.4-F16	F1.6-F22	F2.3-F22
Angle of view	19.4°×14.6°(2/3")	14.3°×10.8°(2/3")	10.1°×7.6°(2/3")
Working Distance*1 [mm]	∞-120	∞-230	∞-500
Operation of focus	Manual	Manual	Manual
Operation of iris	Manual	Manual	Manual
Filter thread [mm]	M25.5×0.5	M25.5×0.5	M25.5×0.5
Mount	C-mount	C-mount	C-mount
Weight (approx.) [g]	40	40	40
Sensor size (std.)*2	2/3"(6.2μm)	2/3"(6.2μm)	2/3"(6.2μm)
Sensor size (max.)*3	2/3"(6.2μm)	2/3"(6.2μm)	2/3"(6.2μm)
TV distortion [%]	-0.19	0.10	0.06
Dimension [mm]	ø29.5×29.5	ø29.5×29.5	ø29.5×29.5


DF6HA-1S




HF9HA-1S




HF25HA-1S




HF35HA-1S




HF12.5HA-1S




HF16HA-1S



HF50HA-1S



HF75HA-1S



*1 From front of lens barrel. *2 Sensor size(std.): Ideal size to maximize the target resolution.


*3 Sensor size(max.): Adaptable sensor size varies depending on the model. Please check the amount of light and resolution on the edges pertaining to your particular application.

HF-SA series, 2/3", 3.45μm, 5MP

- Low distortion
- Large maximum aperture



	HF12.5SA-1	HF16SA-1	HF25SA-1	HF35SA-1	HF50SA-1	HF75SA-1
Focal length [mm]	12.5	16	25	35	50	75
Iris range [F. no]	F1.4-F22	F1.4-F22	F1.4-F22	F1.4-F22	F1.8-F22	F1.8-F22
Angle of view : 2/3"	38.0°x29.0°	30.2°x22.9°	20.8°x15.7°	14.0°x10.5°	9.7°x7.3°	6.7°x5.0°
Working Distance*1 [mm]	∞-100	∞-100	∞-100	∞-200	∞-400	∞-900
Operation of focus	Manual	Manual	Manual	Manual	Manual	Manual
Operation of iris	Manual	Manual	Manual	Manual	Manual	Manual
Filter thread [mm]	M49x0.75	M49x0.75	M49x0.75	M49x0.75	M49x0.75	M49x0.75
Mount	C-mount	C-mount	C-mount	C-mount	C-mount	C-mount
Weight (approx.) [g]	295	285	315	185	240	305
Sensor size (std.)*2	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)
Sensor size (max.)*3	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)	2/3"(3.45μm)
TV distortion [%]	-0.08	0.11	-0.06	0.07	0.08	0.01
Dimension [mm]	ø51x68.5	ø51x70.5	ø51x75.5	ø51x48.5	ø51x55.5	ø51x76




CF-HA series, 1", 9.1μm, 1.5MP

- Low distortion
- Large maximum aperture



	CF12.5HA-1	CF16HA-1	CF25HA-1	CF35HA-1	CF50HA-1	CF75HA-1
Focal length [mm]	12.5	16	25	35	50	75
Iris range [F. no]	F1.4-F22	F1.4-F22	F1.4-F22	F1.4-F22	F1.8-F22	F1.8-F22
Angle of view : 1"	53.1°x41.2°	42.6°x32.8°	29.9°x22.7°	20.3°x15.3°	14.1°x10.6°	9.8°x7.3°
Working Distance*1 [mm]	∞-100	∞-100	∞-100	∞-200	∞-400	∞-900
Operation of focus	Manual	Manual	Manual	Manual	Manual	Manual
Operation of iris	Manual	Manual	Manual	Manual	Manual	Manual
Filter thread [mm]	M49x0.75	M49x0.75	M49x0.75	M49x0.75	M49x0.75	M49x0.75
Mount	C-mount	C-mount	C-mount	C-mount	C-mount	C-mount
Weight (approx.) [g]	290	280	310	180	235	300
Sensor size (std.)*2	1"(9.1μm)	1"(9.1μm)	1"(9.1μm)	1"(9.1μm)	1"(9.1μm)	1"(9.1μm)
Sensor size (max.)*3	1"(9.1μm)	1"(9.1μm)	1"(9.1μm)	1"(9.1μm)	1"(9.1μm)	1"(9.1μm)
TV distortion [%]	0.86	0.79	0.36	0.18	0.20	0.01
Dimension [mm]	ø51x68.5	ø51x70.5	ø51x75.5	ø51x48.5	ø51x55.5	ø51x76



*1 From front of lens barrel. *2 Sensor size(std.): Ideal size to maximize the target resolution.

*3 Sensor size(max.): Adaptable sensor size varies depending on the model. Please check the amount of light and resolution on the edges pertaining to your particular application.

*1 From front of lens barrel. *2 Sensor size(std.): Ideal size to maximize the target resolution.






*3 Sensor size(max.): Adaptable sensor size varies depending on the model. Please check the amount of light and resolution on the edges pertaining to your particular application.

TF series 3CCD, 1/3"

- Ultra-compact, lightweight and robust design
- Supporting 2 MP sensor (TF4XA-1)



	TF2.8DA-8	TF4DA-8	TF4XA-1 2MP	TF8DA-8B	TF15DA-8
Focal length [mm]	2.8	4	4	8	15
Iris range [F. no]	F2.2-F16·Close	F2.2-F16·Close	F2.2-F16·Close	F2.2-F16·Close	F2.2-F16·Close
Angle of view : 1/3"	89.1°×69.3°	64.5°×49.0°	64.5°×49.1°	33.4°×25.1°	18.0°×13.5°
Working Distance*1 [mm]	∞-100	∞-100	∞-100	∞-100	∞-100
Operation of focus	Manual	Manual	Manual	Manual	Manual
Operation of iris	Manual	Manual	Manual	Manual	Manual
Filter thread [mm]	-	M27×0.5	M27×0.5 (INSIDE) M30.5×0.5 (OUTSIDE)	M25.5×0.5	M25.5×0.5
Mount	C-mount	C-mount	C-mount	C-mount	C-mount
Weight (approx.) [g]	75	70	100	60	60
Sensor size (std.)*2	1/3"(6.7μm)	1/3"(6.7μm)	1/3"(6.7μm)	1/3"(6.7μm)	1/3"(6.7μm)
Sensor size (max.)*3	1/3"(6.7μm)	1/3"(6.7μm)	1/3"(6.7μm)	1/3"(6.7μm)	1/3"(6.7μm)
TV distortion [%]	-6.25	-3.77	-4.27	-1.30	-0.31
Dimension [mm]	ø34×47.5	ø29×46.5	ø30.5×44	ø29×39	ø29×39





FE185 series Fisheye lens

- Super wide-angle with a 185° field of view
- 2 models for 1" and 2/3"
- Supporting 5 MP sensor




	FE185C086HA-1	FE185C057HA-1
Focal length [mm]	2.7	1.8
Iris range [F. no]	F1.8-F16	F1.4-F16
Angle of view : 1"	185.0°×185.0°(ø8.6mm)	185.0°×185.0°(ø5.7mm)
Angle of view : 2/3"	185.0°×140.6°	185.0°×154.1°
Angle of view : 1/2"	136.3°×102.3°	154.1°×115.4°
Working Distance*1 [mm]	∞-200	∞-100
Operation of focus	Fixed	Fixed
Operation of iris	Manual	Manual
Mount	C-mount	C-mount
Weight (approx.) [g]	160	135
Sensor size (std.)*2	-	-
Sensor size (max.)*3	1"(5μm)	2/3"(3.45μm)
Dimension [mm]	ø56.5×60.5	ø56.5×60.3




■ Simulation images

FE185C086HA-1



FE185C057HA-1



*1 From front of lens barrel. *2 Sensor size(std.): Ideal size to maximize the target resolution.

*3 Sensor size(max.): Adaptable sensor size varies depending on the model. Please check the amount of light and resolution on the edges pertaining to your particular application.

*1 From front of lens. *2 Sensor size(std.): Ideal size to maximize the target resolution.

*3 Sensor size(max.): Adaptable sensor size varies depending on the model. Please check the amount of light and resolution on the edges pertaining to your particular application.

FUJINON Lens Shooting Range Chart

CF-ZA-1S series

CF8ZA-1S

Working Distance [mm]	Optical Magnification	Extension Tube [mm]	Field of View [mm]					
			1.1"		1"		2/3"	
H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]
1000	0.008x	-	1888.5	1361.5	1684.7	1221.8	1112.6	822.2
950	0.009x	-	1795.5	1294.5	1601.8	1161.6	1057.8	781.7
900	0.009x	-	1702.5	1227.4	1518.8	1104.1	1003.0	741.2
850	0.010x	-	1609.6	1160.3	1435.9	1041.2	948.2	700.7
800	0.010x	-	1516.6	1093.3	1352.9	981.0	893.4	660.2
750	0.011x	-	1423.6	1026.2	1269.9	920.9	838.6	619.7
700	0.012x	-	1330.6	959.2	1187.0	860.7	783.7	579.1
650	0.013x	-	1237.7	892.1	1104.0	800.5	726.9	538.6
600	0.014x	-	1144.7	825.0	1021.1	740.3	674.1	498.1
550	0.015x	-	1051.7	758.0	938.1	680.1	619.3	457.6
500	0.016x	-	958.7	690.9	855.2	619.9	564.5	417.1
450	0.018x	-	865.8	623.9	772.2	559.8	509.7	376.6
400	0.020x	-	772.8	556.8	689.2	499.6	454.9	336.1
350	0.023x	-	679.8	489.7	606.3	439.4	400.1	295.6
300	0.026x	-	586.8	422.7	523.3	379.2	345.2	255.0
250	0.031x	-	493.8	355.6	440.3	319.0	290.4	214.5
200	0.039x	-	400.8	288.5	357.3	258.8	235.6	174.0
150	0.050x	-	307.8	221.4	274.4	198.6	180.8	133.5
100	0.073x	-	214.8	154.3	191.3	138.4	125.9	92.9

CF12ZA-1S

Working Distance [mm]	Optical Magnification	Extension Tube [mm]	Field of View [mm]					
			1.1"		1"		2/3"	
H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]
1000	0.012x	-	1238.5	906.0	1112.2	815.2	743.6	551.4
950	0.013x	-	1177.7	861.5	1057.6	775.1	707.1	524.3
900	0.013x	-	1116.9	817.1	1003.0	735.1	670.6	497.2
850	0.014x	-	1056.2	772.6	948.4	695.1	634.1	470.2
800	0.015x	-	995.4	728.1	893.8	655.0	597.5	443.1
750	0.016x	-	934.6	683.6	839.3	615.0	561.0	416.0
700	0.017x	-	873.8	639.1	784.7	575.0	524.5	388.9
650	0.019x	-	813.1	594.6	730.1	535.0	488.0	361.8
600	0.020x	-	752.3	550.1	675.5	494.9	451.5	334.7
550	0.022x	-	691.5	505.7	620.9	454.9	414.9	307.6
500	0.024x	-	630.7	461.2	566.3	414.9	378.4	280.6
450	0.026x	-	570.0	416.7	511.7	374.8	341.9	253.5
400	0.030x	-	509.2	372.2	457.1	334.8	305.4	226.4
350	0.034x	-	448.4	327.7	402.5	294.7	268.8	199.3
300	0.039x	-	387.6	283.2	347.9	254.7	232.3	172.2
250	0.046x	-	326.8	236.6	293.2	214.6	195.7	145.1
200	0.057x	-	265.9	194.1	238.6	174.6	159.2	118.0
150	0.074x	-	205.0	149.5	183.9	134.5	122.6	90.8
100	0.105x	-	144.0	104.9	129.1	94.3	86.0	63.7

HF-12M series

HF818-12M

Working Distance [mm]	Optical Magnification	Extension Tube [mm]	Field of View [mm]					
			2/3"		1/2"		1/3"	
H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]
1000	0.008x	-	1099.9	818.7	793.5	593.5	593.5	444.5
950	0.009x	-	1045.7	778.3	754.4	564.2	564.2	422.6
900	0.013x	-	991.5	738.0	715.3	535.0	535.0	400.7
850	0.014x	-	937.3	697.7	676.2	505.7	505.7	378.8
800	0.010x	-	883.2	657.3	637.1	476.5	476.5	356.9
750	0.011x	-	829.0	617.0	598.0	447.3	447.3	335.0
700	0.011x	-	774.8	576.7	558.9	418.0	418.0	313.1
650	0.012x	-	720.6	536.3	519.8	388.8	388.8	291.2
600	0.013x	-	666.4	496.0	480.7	359.5	359.5	269.3
550	0.015x	-	612.3	455.6	441.6	330.3	330.3	247.4
500	0.016x	-	558.1	415.3	402.5	301.0	301.0	225.5
450	0.018x	-	503.9	375.0	363.4	271.8	271.8	203.5
400	0.020x	-	449.7	334.6	324.4	242.5	242.5	181.6
350	0.023x	-	395.5	294.3	285.3	213.3	213.3	159.7
300	0.026x	-	341.4	254.0	246.2	184.1	184.1	137.8
250	0.031x	-	287.2	213.6	207.1	154.8	154.8	115.9
200	0.038x	-	233.0	173.3	168.0	125.6	125.6	94.0
150	0.050x	-	178.8	133.0	128.9	96.3	96.3	72.1
100	0.072x	-	124.6	92.6	89.8	67.1	67.1	50.2

HF1218-12M

Working Distance [mm]	Optical Magnification	
-----------------------	-----------------------	--

HF-XA-5M series

HF6XA-5M

Working Distance [mm]	Optical Magnification	Extension Tube	Field of View [mm]					
			2/3"		1/2"		1/3"	
[mm]	H	V	H	V	H	V	H	V
1000	0.006x	-	1548.2	1126.4	1089.5	802.1	802.1	594.9
950	0.006x	-	1471.8	1079.9	1035.7	762.5	762.5	565.6
900	0.007x	-	1395.5	1015.3	982.0	722.9	722.9	536.3
850	0.007x	-	1319.1	959.8	928.3	683.4	683.4	506.9
800	0.008x	-	1242.8	904.2	874.6	643.8	643.8	477.6
750	0.008x	-	1166.5	848.7	820.8	604.3	604.3	448.2
700	0.009x	-	1090.1	793.1	767.1	564.7	564.7	418.9
650	0.009x	-	1013.8	737.6	713.4	525.2	525.2	386.9
600	0.010x	-	937.4	682.0	659.6	485.6	485.6	360.2
550	0.011x	-	861.1	626.5	605.9	446.1	446.1	330.9
500	0.012x	-	784.8	570.9	552.2	406.5	406.5	301.5
450	0.013x	-	708.4	515.4	498.5	367.0	367.0	272.2
400	0.015x	-	632.1	459.8	444.7	327.4	327.4	242.9
350	0.017x	-	555.7	404.3	391.0	287.8	287.8	213.5
300	0.020x	-	479.4	348.7	337.3	248.3	248.3	184.2
250	0.024x	-	403.0	293.2	283.5	208.7	208.7	154.8
200	0.029x	-	326.7	237.6	229.8	169.2	169.2	125.5
150	0.038x	-	250.4	182.1	176.1	129.6	129.6	96.2
100	0.055x	-	174.0	126.5	122.4	90.1	90.1	66.8

HF12XA-5M

Working Distance [mm]	Optical Magnification	Extension Tube	Field of View [mm]					
			1/1,2"		2/3"		1/2"	
[mm]	H	V	H	V	H	V	H	V
1000	0.012x	-	913.0	673.6	740.5	548.9	531.8	396.2
950	0.013x	-	868.0	640.4	704.0	521.9	505.6	376.7
900	0.014x	-	823.0	607.2	667.5	494.8	479.4	357.2
850	0.014x	-	778.0	574.0	631.0	467.8	453.2	337.7
800	0.015x	-	733.0	540.8	594.5	440.7	427.0	318.1
750	0.016x	-	688.0	507.6	558.0	413.7	400.8	298.6
700	0.017x	-	643.1	474.5	521.6	386.6	374.6	279.1
650	0.019x	-	598.1	441.3	485.1	359.6	348.3	259.6
600	0.020x	-	553.1	408.1	448.6	332.5	322.1	240.0
550	0.022x	-	508.1	374.9	412.1	305.5	295.9	220.5
500	0.024x	-	463.1	341.7	375.6	278.4	269.7	201.0
450	0.027x	-	418.2	308.5	339.1	251.4	243.5	181.5
400	0.030x	-	373.2	275.3	302.6	224.3	217.3	161.9
350	0.034x	-	328.2	242.1	266.2	197.3	191.1	142.4
300	0.039x	-	283.2	208.9	229.7	170.2	164.9	122.9
250	0.047x	-	238.2	175.7	193.2	143.2	138.7	103.4
200	0.058x	-	193.2	142.5	156.7	116.1	112.5	83.8
150	0.075x	-	148.3	109.3	120.2	89.1	86.3	64.3
100	0.108x	-	103.3	76.1	83.7	62.0	60.1	44.8

HF25XA-5M

Working Distance [mm]	Optical Magnification	Extension Tube	Field of View [mm]					
			1/1,2"		2/3"		1/2"	
[mm]	H	V	H	V	H	V	H	V
1000	0.025x	-	436.0	326.6	357.6	267.9	259.8	194.7
950	0.026x	-	414.6	310.5	340.0	254.7	247.0	185.1
900	0.027x	-	393.1	294.4	322.4	241.5	234.2	175.5
850	0.029x	-	371.7	278.4	304.8	228.4	221.4	166.0
800	0.031x	-	350.3	262.3	287.2	215.2	208.6	156.4
750	0.033x	-	328.8	246.2	269.6	202.0	195.9	146.8
700	0.035x	-	307.4	230.2	252.0	188.8	183.1	137.2
650	0.038x	-	285.9	214.1	234.5	175.6	170.3	127.6
600	0.041x	-	264.5	198.1	216.9	162.5	157.5	118.1
550	0.044x	-	243.1	182.0	199.3	149.3	144.7	108.5
500	0.049x	-	221.6	165.9	181.7	136.1	132.0	98.9
450	0.054x	-	200.2	149.9	164.1	122.9	119.2	89.3
400	0.060x	-	178.8	133.8	146.5	109.7	106.4	79.7
350	0.068x	-	157.3	117.7	128.9	96.6	93.6	70.2
300	0.079x	-	135.9	101.7	111.4	83.4	80.8	60.6
250	0.094x	-	114.4	85.6	93.8	70.2	68.1	51.0
200	0.116x	-	93.0	69.5	76.2	57.0	55.3	41.4
150	0.151x	-	71.5	53.5	58.6	43.8	42.5	31.8
100	0.216x	-	50.1	37.4	41.0	30.7	29.7	22.3

HF50XA-5M

Working Distance [mm]	Optical Magnification	Extension Tube	Field of View [mm]					
			1.1"		2/3"		1/2"	
[mm]	H	V	H	V	H	V	H	V
1000	0.048x	-						

HF-SA series

HF12.5SA-1

Working Distance [mm]	Optical Magnification	Extension Tube [mm]	Field of View [mm]					
			2/3"		1/2"		1/3"	
[mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]
1000	0.013x	-	705.4	528.0	511.9	383.3	383.3	287.2
950	0.013x	-	670.9	502.2	486.9	364.6	364.6	273.2
900	0.014x	-	636.4	476.4	461.8	345.8	345.8	259.1
850	0.015x	-	601.9	450.5	436.8	327.1	327.1	245.1
800	0.016x	-	567.5	424.7	411.8	308.3	308.3	231.0
750	0.017x	-	533.0	398.9	386.7	289.6	289.6	217.0
700	0.018x	-	498.5	373.1	361.7	270.8	270.8	202.9
650	0.019x	-	464.1	347.3	336.7	252.1	252.1	188.9
600	0.021x	-	429.6	321.5	311.7	233.3	233.3	174.8
550	0.022x	-	395.1	295.6	286.6	214.6	214.6	160.8
500	0.025x	-	360.6	269.8	261.6	195.8	195.8	146.7
450	0.027x	-	326.2	244.0	236.6	177.1	177.1	132.7
400	0.030x	-	291.7	218.2	211.5	158.3	158.3	118.6
350	0.034x	-	257.2	192.4	186.5	139.6	139.6	104.6
300	0.040x	-	222.8	166.6	161.5	120.8	120.8	90.5
250	0.047x	-	188.3	140.7	136.4	102.1	102.1	76.5
200	0.058x	-	153.8	114.9	111.4	83.4	83.4	62.4
150	0.075x	-	119.3	89.1	86.4	64.6	64.6	48.4
100	0.105x	-	84.9	63.3	61.3	45.9	45.9	34.3

HF25SA-1

Working Distance [mm]	Optical Magnification	Extension Tube [mm]	Field of View [mm]					
			2/3"		1/2"		1/3"	
[mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]
1000	0.023x	-	378.4	283.4	274.8	205.9	205.9	154.4
950	0.025x	-	360.0	269.6	261.4	195.9	195.9	146.8
900	0.026x	-	341.6	255.9	248.1	185.9	185.9	139.3
850	0.027x	-	323.2	242.1	234.7	175.9	175.9	131.8
800	0.029x	-	304.9	228.3	221.4	165.9	165.9	124.3
750	0.031x	-	286.5	214.5	208.0	155.9	155.9	116.8
700	0.033x	-	268.1	200.8	194.7	145.8	145.8	109.3
650	0.035x	-	249.7	187.0	181.3	135.8	135.8	101.8
600	0.038x	-	231.3	173.2	167.9	125.8	125.8	94.3
550	0.042x	-	212.9	159.4	154.6	115.8	115.8	86.8
500	0.045x	-	194.6	145.7	141.2	105.8	105.8	79.3
450	0.050x	-	176.2	131.9	127.9	95.8	95.8	71.8
400	0.056x	-	157.8	118.1	114.5	85.8	85.8	64.3
350	0.063x	-	139.4	104.3	101.1	75.8	75.8	56.8
300	0.073x	-	121.0	90.5	87.8	65.7	65.7	49.3
250	0.086x	-	102.6	76.8	74.4	55.7	55.7	41.8
200	0.105x	-	84.2	63.0	61.1	45.7	45.7	34.3
150	0.135x	-	65.9	49.2	47.7	35.7	35.7	26.8
100	0.187x	-	47.5	35.4	34.3	25.7	25.7	19.2

HF16SA-1

Working Distance [mm]	Optical Magnification	Extension Tube [mm]	Field of View [mm]					
			2/3"		1/2"		1/3"	
[mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]	H [mm]	V [mm]
1000	0.016x	-	556.0	416.9	404.3	303.1	303.1	227.2
950	0.017x	-	529.1	396.7	384.7	288.4	288.4	216.2
900	0.018x	-	502.1	376.5	365.1	273.7	273.7	205.2
850	0.019x	-	475.2	356.3	345.5	259.0	259.0	194.2
800	0.020x	-	448.2	336.0	325.8	244.3	244.3	183.1
750	0.021x	-	421.3	315.8	306.2	229.6	229.6	172.1
700	0.022x	-	394.3	295.6	286.6	214.8	214.8	161.1
650	0.024x	-	367.4	275.4	267.0	200.1	200.1	150.0
600	0.026x	-	340.4	255.2	247.4	185.4	185.4	139.0
550	0.028x	-	313.5	234.9	227.8	170.7	170.7	128.0
500	0.031x	-	286.5	214.7	208.2	156.0	156.0	117.0
450	0.034x	-	259.6	194.5	188.6	141.3	141.3	105.9
400	0.038x	-	232.6	174.3	169.0	126.6	126.6	94.9
350	0.043x	-	205.7	154.0	149.4	111.9	111.9	83.9
300	0.049x	-	178.7	133.8	129.7	97.2	97.2	72.8
250	0.058x	-	151.8	113.6	110.1	82.5	82.5	61.8
200	0.071x	-	124.8	93.4	90.5	67.8	67.8	50.8
150	0.091x	-	97.9	73.1	70.9	53.1	53.1	39.8
100	0.126x	-	70.9	52.9	51.3	38.4	38.4	28.7

CF-HA series

CF12.5HA-1

Working Distance [mm]	Optical Magnification	Extension Tube [mm]	Field of View [mm]					
			1"		2/3"		1/2	