

# Image Delay Time

BRC-X400/BRC-X401  
SRG-X400/SRG-201M2  
SRG-X120/SRG-HD1M2

Sony Imaging Products & Solutions Inc.  
October 2019

# Image Delay Time

Product Name	Video Format	Maximum Image Delay Time[V]	1V[ms]
BRC-X400/BRC-X401	3840x2160/29.97p	2.62	33.36
	3840x2160/25p	2.65	40.00
	3840x2160/23.98p	2.42	41.70
SRG-X400/SRG-201M2 SRG-X120/SRG-HD1M2	1920x1080/59.94p(A)	2.73	16.68
	1920x1080/59.94p(B)	2.73	16.68
	1920x1080/59.94i	2.71	16.68
	1920x1080/29.97p	1.87	33.36
	1280x720/59.94p	2.71	16.68
	1920x1080/50p(A)	2.72	20.00
	1920x1080/50p(B)	2.72	20.00
	1920x1080/50i	2.71	20.00
	1920x1080/25p	1.88	40.00
	1280x720/50p	2.73	20.00
1920x1080/23.98p	1.63	41.70	

\* The shutter speed is measured with the default value.  
(For 23.98p, shutter speed 1/48 is the default value.)

Note)

1) It cannot be guaranteed and may differ from actual.

