

導播機

HD 12通道導播機**SE-3200**

影像系統	Full HD
影像格式	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz
影像處理	SDI: 4:2:2 HDMI: YUV 4:2:2, RGB: 4:4:4
輸入設定	All 12, repeatable
影像輸入	8x SDI, 4x HDMI
相容HD/SD	----
電腦連結	4 via HDMI
影像輸出	6x SDI Outputs assignable: Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12, STILL 1, STILL 2, Flex source 3x HDMI assignable: Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12, STILL 1, STILL 2, Flex source
下轉輸出	1x SDI
多分割監看	HDMI & SDI assignable
聲音輸入	4x Balanced XLR
聲音輸出	2x Balanced XLR
支持聲音軌數	Input 2 channels, Output 4 channels
聲音延遲	Up to 16 fields or 8 frames per channel
影音像同步切換	Yes
影像去背	4
字幕機	Yes, CG-200 software free download
USK	4x Keyer support Chromakey/ Linear/ Luma Key
DSK	2x DSK support Lumakey & Linear key (Key / Fill)
子母畫面	8 (4x PIP, 4x Flex Source)
LOGO顯示	2
圖片顯示	999+
特效	DVE, FTB, Cut, 32 Wipe with border
過場預覽	Full transitions preview
同步訊號輸入/出	Built-in Genlock Support external sync with loop thru
Tally輸出	1x D-sub 25pin, dual color
電腦控制	RS-232 / DVIP (Ethernet)
Camera Control	----

混音器	----
Storage	----
Recording File System	----
Recording File Format	----
Video Encode	----
Audio Encode	----
Streaming Protocol	----
Firmware Update	Ethernet
特別功能	4 User Memory Preset Free Virtual Set and Stinger transition included
外型	2 units, 2RU rack-mount mainframe
尺寸	433 x 312 x 76 mm (switcher) 432 x 252 x 88 mm (main unit)
重量	4 kg
電源	DC 12V, 69W
操作溫度	0~40 °C
附件	1 x SE-3200 Main Unit 1 x SE-3200 Control Board 2 x AD Switch DC 12V 1 x AC Cord 1 x DB9P TO DB9P Cable 12 x Screw 2 x 2U Ear Rack