



# 1745BOW

## Air

### Bow Case

The new Pelican™ Air 1745 Bow Case is the long-awaited bow case solution from the leader in premium protection. This case was expertly designed to meet the unique needs of the most demanding bow hunters. Designed with the trademark Pelican™ Air case construction, it's up to 40% lighter weight than the competition, minimizing additional travel costs. The exterior features six heavy duty, push button latches (including two TSA approved locking latches), 4 stainless steel lock hasps, and wheels for easy transit. The interior components provide modular storage, allowing for a wide range of configurations for your unique bow and accessory kit.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- 6 press and pull latches with 2 TSA approved locking latches for security
- Molle Strap System creates a customizable interior
- Added divider provides protection for your bow and features a large storage pocket on the top
- Includes: 2 foam arrow holders, 2 small foam bumpers, 2 large foam bumpers, 2 arrow tube straps, 2 small accessory pouches, 6 bungee cords, 1 padded divider
- Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2</sup>™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



## DIMENSIONS

<b>Interior (LxWxD)</b>	44.01 x 16.77" x 7.94 (111.8 x 42.6 x 20.2 cm)
<b>Exterior (LxWxD)</b>	46.69 x 19.36" x 8.73 (118.6 x 49.2 x 22.2 cm)
<b>Int Volume</b>	3.39 ft <sup>3</sup> (0.096 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

## MATERIALS

<b>Body</b>	Proprietary Polypropylene Blend
<b>Latch</b>	ABS
<b>O-Ring</b>	EPDM
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

## COLORS

- Black

## WEIGHT

<b>Weight With Bow Interior</b>	23.15 lbs (10.5 kg)
---------------------------------	---------------------

## TEMPERATURE

---

**Minimum Temperature** -60°F (-51.1 °C)


**Maximum Temperature** 160°F (71.1 °C)

## ACCESSORIES

---



**1500CI**  
Corrosion Intercept Kit



**LGMT-001A**  
Air Case Roof Mount

---

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 03-26-25*