

Halogen non-reflector

6390 30W G5.3 10.8V 1CT

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 - the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

Product data

• General Characteristics

Philips Code	6390
ANSI Code	DZA
LIF Code	-
Cap-Base	G5.3
Bulb Material	Quartz-UV Open
Filament Shape	Flat
Operating Position	s90
Main Application	Projection
Life to 50% failures	1000 hr

• Light Technical Characteristics

Color Rendering Index	100 Ra8			
Color Temperature Technical	3100 K			
Luminous Flux Lamp	570 Lm			

• Electrical Characteristics

Lamp Wattage	30 W
Voltage	10.8 V

• Luminaire Design Requirements

Pinch Temperature	400 (max) C
Bulb Temperature	900 (max) C

Product Dimensions

Diameter D Light Center Length 1

Pin Diameter P

Filament Dimensions (WxH) [mm]

26.75 (min), 27 (nom), 27.25 (max) mm 1.45 (min), 1.50 (nom), 1.55 (max) mm 3.5×1.25

9 (max) mm


6.500 kg

• Product Data

Order code Full product code Full product name Order product name Pieces per pack Packing configuration Packs per outerbox Bar code on pack -EAN1 Bar code on intermediate packing -EAN2 Bar code on outerbox - EAN3 Logistic code(s) -12NC Net weight per piece 822234361802 822234361802 6390 30W G5.3 10.8V 1CT 6390 30W G5.3 10.8V 1CT/10X10F 10X10F 100 8711500410085 8711500422415 8711500422422 822234361802

PHILIPS

Dimensional drawing



6390 30W G5.3 10.8V 1CT

Product	C (Norm)	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)	P (Min)	P (Norm)	P (Max)
6390 30W G5.3 10.8V	-	-	9	26.75	27	27.25	1.45	1.50	1.55





G5.3



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting